

JOB NAME:

CONTRACTOR:

DATE:

STINGER[®]

STAPLEPAC[®]



FUNCTION Designed for installation of synthetic underlayment, roofing felt, housewrap, and foam board insulation
For indoor or outdoor applications

FEATURES Collated Fasteners meet or exceed the ASTM F1667 Standard (if applicable)
StaplePac[®] tested per ASTM D7869-17; total Xenon Arc exposure exceeding 550 hours without cracking or whitening and should meet or exceed the 6-month exposure warranty of Stinger EXO underlayments

CORROSION Electro Galvanized (EG) in accordance with ASTM A641 standards for low level corrosion resistance

CAUTION  Proper personal protection equipment (PPE), i.e. safety glasses, must be worn during installation of any fastener
Electro Galvanized (EG) shall not be used in cedar, cement board, or redwood
Electro Galvanized (EG) shall not be used within 3000 feet of saltwater

TECHNICAL	Cap Diameter	Cap Flat-to-Flat	Cap Edge Lip	Staple Crown	Staple Leg Length	Staple Gauge	
	1 in ±.063	0.923 in	0.035 in	7/16 in	5/8 - 1-1/2 in	18	
PRODUCT	Staple QTY	Box Count QTY	Cap Count	5/8" EG SKU	7/8" EG SKU	1-1/4" EG SKU	1-1/2" EG SKU
	100	20 Strips	200 / 10 reels	0136024	0136044	0136074	0136094
COMPATIBLE TOOLS							
	Stinger CS150 Discontinued 2018		Stinger CS150B #0136012				

TECHNICAL	Cap Diameter	Cap Flat-to-Flat	Cap Edge Lip	Staple Crown	Staple Leg Length	Staple Gauge	
	1 in ±.063	0.923 in	0.035 in	3/8 in	3/8 in	21	
PRODUCT	Staple QTY	Box Count QTY	Cap Count	3/8" EG SKU			
	84	24 strips	168 / 12 reels	0136420			
COMPATIBLE TOOLS							
	Stinger CH38A #0136401		Stinger CH38-2 #0136400				